## PATENT ABSTRACTS OF JAPAN

(11)Publication number:

03-125807

(43)Date of publication of application: 29.05.1991

(51)Int.CI.

F23D 14/18

F23D 11/40 F23D 14/02

(21) Application number: **01-261813** 

(71)Applicant:

**BABCOCK HITACHI KK** 

(22) Date of filing:

06.10.1989

(72)Inventor:

**MATSUO YOSHIO ICHIYANAGI HIROSHI** 


**IMAMURA MITSUO** MATSUDA MASAYUKI


## (54) CATALYTIC BURNER

## (57) Abstract:

PURPOSE: To make a catalyst for combustion highly active at low temperature and highly heat-resistant at high temperature and at the same time make it possible to burn under a high load by arranging mutually coaxially a catalytic combustion cylinder inside of an outer cylinder and a gas phase combustion cylinder which consists of a heat shielding body inside of the catalytic combustion cylinder and supplying fuel and air from one end section of the catalytic burner into both cylinders.

CONSTITUTION: A burner 2 consists of a double construction body which has an outer cylinder 8 which is open at its one end and an inner cylinder 9 which is open at its both ends, and in the inside of the inner cylinder 9 a catalyst body 14 for combustion and a heat shielding layer 15 inside of the catalyst body 14 are respectively arranged cylindrically. A fuel supply pipe 6 which pierces through the closed end section of the outer cylinder 8 is connected to a fuel supply port 13 through a control valve 22 inside of an air flow inlet 11 which is formed by a catalyst holding member 16, and between the inside of the air flow-in port 10 of the inner cylinder 9 and the outside of an air flow inlet 11 which is formed by the catalyst holding member 16 the fuel supply pipe 6 is connected to a fuel





supply port 12 through a control valve 21. In the catalyst body 14 for combustion and a vapor phase combustion chamber 18 temperature sensors 19 and 20 are provided respectively, and by their output signals control valves 21 and 22 are controlled. Further, between the outer cylinder 8 and inner cylinder 9 of the burner 2 compressed air 5 is sent from a compressor 1.

Searching PAJ 2/25/03 12:19 PM

## LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2000 Japan Patent Office